







Table 25. Ultrafast Recovery Rectifiers (continued)

**I_O, AVERAGE RECTIFIED FORWARD CURRENT (Amperes)							
8	12	15		16		25	
221B-01 (TO-220AC) Plastic 	56-03 (DO-203AA) Metal 	221B-01 (TO-220AC) Plastic 	56-03 (DO-203AA) Metal 	221A-04 (TO-220AB) Plastic 		56-03 (DO-203AA) Metal 	
MUR805	BYW30-50	MUR1505	BYW81-50	BYW51-50	MUR1605CT	BYV32-50	BYW31-50
MUR810	BYW30-100	MUR1510	BYW81-100	BYW51-100	MUR1610CT	BYV32-100	BYW31-100
MUR815	BYW30-150	MUR1515	BYW81-150	BYW51-150	MUR1615CT	BYV32-150	BYW31-150
MUR820	BYW30-200	MUR1520	BYW81-200	BYW51-200	MUR1620CT	BYV32-200	BYW31-200
MUR830		MUR1530			MUR1630CT		
MUR840		MUR1540			MUR1640CT		
MUR850		MUR1550			MUR1650CT		
MUR860		MUR1560			MUR1660CT		
MUR870E†							
MUR880E†							
MUR890E†							
MUR8100E†							
100	200	200	200	100	100	150	320
150	120	150	120	130	150	120	120
175	175	175	150	175	175	150	150
35/60/100	35	35/60	35	35	35	35	50

** I_O is total device output.

† "E" Series is specified reverse avalanche energy series.